



## The Simplest Labelling Solution On The Market, Tested To The Highest Specs.

### Fox-Flo Labels



<b>Material</b>	Silver Fox Fox-Flo® Material
<b>Thickness</b>	1mm
<b>RoHS (EU 2002/95/EC)</b>	RoHS Compliant

Fox-Flo® zero halogen labels are flame retardant, halogen free and intended for use in identification purposes.  
**MAJOR TEST DONE ON IT**  
 UV Weathering 8000 hrs , High temp 2000 hrs @ 70°C to 100°C, H2S Sour Gas Exposure, Salt Mist Spray , Oxygen Index , Vertical Burning Test, IMO FTPC Part 2 and Part 5, Chemical /Solvent Resistance etc

### Tie On Cable Labels



<b>Material</b>	Polyester
<b>Thickness</b>	175 microns
<b>Standard Sizes</b>	60 x 13mm, 90mm x 13mm, 90mm x 20mm
<b>RoHS (EU 2002/95/EC)</b>	RoHS Compliant

**MAJOR TESTS DONE**  
 Moisture Resistance ,High Temperature 2000 hours @ 70°C to 100°C ,Hydrogen Sulphide ,UV Weathering 500 hours, Salt Mist Spray, Chemical /Solvent Resistance etc

### Legend™ LHS Premium Heatshrink



<b>Material</b>	Polyolefin
<b>Shrink Ratio</b>	3:1
<b>Min. Shrink Temperature</b>	90°C (full recovery)
<b>Dielectric Strength</b>	≥ 37 kV/mm
<b>Standard Colours</b>	Yellow, White
<b>RoHS (EU 2002/95/EC)</b>	RoHS Compliant

**MAJOR TESTS DONE**  
 Moisture Resistance , Low Temperature 72 hours @ -40°C, High Temperature 2000 hours @ 70°C to 100°C, Hydrogen Sulphide, UV Weathering 1000 hours, Salt Mist Spray etc.

### Legend™ LNST NON - Shrink - Tubing



<b>Material</b>	PVC
<b>Standard Colours</b>	Yellow, White(Blue on selected sizes)
<b>RoHS (EU 2002/95/EC)</b>	RoHS Compliant

**MAJOR TESTS DONE**  
 Moisture Resistance , Low Temperature 72 hours @ -40°C, High Temperature 500hours@ 70°C, Hydrogen Sulphide, UV Weathering 500 hours, Salt Mist Spray etc

### Prolab® Standard Laser Wrap-around Cable Labels



<b>Material</b>	Self-adhesive Matt Polyester
<b>Standard Colours</b>	25 microns
<b>RoHS (EU 2002/95/EC)</b>	RoHS Compliant

**MAJOR TESTS DONE**  
 High Temperature 1000 hours @ 70°C to 100°C, Hydrogen Sulphide, UV Weathering, Salt Mist Spray etc

### 2-Part Labelling System



<b>Printing Method</b>	Silver Fox DTP-1 Thermal Printer
<b>Thermal Ribbon</b>	Silver Fox TSR3
<b>Material</b>	Polypropylene
<b>Standard Colours</b>	White
<b>RoHS (EU 2002/95/EC)</b>	RoHS Compliant

**MAJOR TESTS DONE**  
 Moisture Resistance , High Temperature 1000 hours @ 70°C to 100°C, Hydrogen Sulphide, UV Weathering , Salt Mist Spray etc

### Prolab® Optical Fibre Flag Labels



<b>Material</b>	36 micron self-adhesive polyester
<b>Standard Colours</b>	White
<b>Sheet Sizes</b>	A4
<b>RoHS (EU 2002/95/EC)</b>	RoHS Compliant

**MAJOR TESTS DONE**  
 Moisture Resistance , High Temperature 2000 hours @ 70°C to 100°C, Hydrogen Sulphide, UV Weathering 500 hours , Salt Mist Spray, Chemical / Solvent Resistance etc


### Stainless Steel Labels



<b>Material</b>	Type 304 or 316 Stainless Steel
<b>Chemical / UV Resistance</b>	Excellent

**OVERVIEW**  
 Our Stainless Steel engraved labels are ideal for all applications. They are produced in our factory to your exact requirements. We can produce them with whatever information is required, in one or more lines and with different font styles/sizes (even on the same label). There are various sizes available.

### Traffolyte Engraved Labels



<b>Material</b>	High Pressure Plastic Laminate
<b>Adhesive</b>	High-tack Acrylic Adhesive
<b>RoHS (EU 2002/95/EC)</b>	RoHS Compliant

**OVERVIEW**  
 Our Traffolyte engraved labels are made from high pressure plastic laminate, screw holes can be added if required. Size, message and colour are matched to your specific requirements.

### Prolab® P/TAG Self-Adhesive Equipment Labels



<b>Material</b>	Self-Adhesive Polyester
<b>Thickness</b>	50 microns
<b>RoHS (EU 2002/95/EC)</b>	RoHS Compliant

**MAJOR TEST DONE**  
 Moisture Resistance, High temperature, Hydrogen Sulphur, Salt Mist Spray, UV Weathering 3000 hrs.

### Prolab® Asset Labels



<b>Printing Method</b>	Silver Fox DTP-1 Thermal Printer
<b>Thermal Ribbon</b>	Silver Fox TSR3
<b>Material</b>	Self-adhesive Polyester
<b>Thickness</b>	56 microns
<b>Standard Colours</b>	White, Silver
<b>Standards Sizes</b>	60mm x 10mm
<b>RoHS (EU 2002/95/EC)</b>	RoHS Compliant

**MAJOR TESTS DONE**  
 Low Temperature 72 hours @ -40°C, High Temperature 2000 hours @70°C to 100°C, Hydrogen Sulphide, UV Weathering 2000 hours (Silver), UV Weathering 3000 hours (White), Salt Mist Spray etc

### Customers:

